

عنوان مقاله:

THE EFFECT OF SOURCE DISTANCE IN DETERMINATION OF SITESPECIFIC HAZARD SPECTRUM

محل انتشار:

هفتمین کنفرانس بین المللی زلزله شناسی و مهندسی زلزله (سال: 1394)

تعداد صفحات اصل مقاله: 8

نویسندگان:

Mohammad Reza SOGHRAT - *PhD student, International institute of earthquake engineering and seismology (IIEES),
Tehran, Iran*

Mansour ZIYAEIFAR - *Associate Professor, International institute of earthquake engineering and seismology (IIEES),
Tehran, Iran*

خلاصه مقاله:

Some elements of the completed structures that supply strength, stiffness and stability may not be existed at the special phases of the construction procedure. Incomplete structures must have enough structural integrity in various stages of construction to ensure stability and resistance against the seismic loads. Stability of the partially completed structures and the probability of progressive collapse should be considered in seismic design. For seismic design during construction, it seems that we should use reduced seismic load compared to design spectrum (with return period, T_r , of 475 years). To achieve this goal, we should estimate the site-specific spectrum. In this study, we use the probabilistic seismic hazard analysis (PSHA) to determine the uniform hazard spectrum by focusing on short return periods. In short return periods, the low intensity measures of the earthquakes will be important. The measures may be originated from large distant or small near earthquakes. Ground Motion Prediction Equations (GMPEs) are an important parameter in PSHA. We select a GMPE which can cover the distance up to 400 km. It is clear that the radius of imaginary circle around the desired site may be an effective factor in evaluation of seismic hazard (especially in spectrum with short return period) which it is generally considered about 150 km. In this study; we consider three different radii around the site (100, 200, 400 km) to control the sensitivity of result to the radius parameter. It should be noted that two sites (Tehran; very high seismic zone and Arak; moderate seismic zone) in Iran are chosen to analyze. It is shown that the controlling scenarios in spectrum with short return periods for Tehran site are nearer than Arak. Also, it can be concluded that in lower seismicity zones, considered radius larger than 200 km has significant effect on spectrum with short return periods that are important in during construction structure.

کلمات کلیدی:

Short Return Period, PSHA, Gmpes, Seismicity Zones

لینک ثابت مقاله در پایگاه سیویلیکا:

<https://civilica.com/doc/1132706>



